

Motostivuitoar (forklift) AUSA CH130 – oferit de noatransconst.com si stivuitoarbz.ro
as offered by noatransconst.com and stivuitoarbz.ro

An de fabricatie (Year of manufacture): 2001
Sarcina de ridicare (Lifting capacity): 1.3t
Inaltime de ridicare (Lifting height): 3m
Alte detalii: duplex, translatie, 4x4
Pret (Price): 6000 € (euro)



INFORMATII GENERALE (GENERAL INFO)

Tip combustibil (Fuel type)	Motorina (Petrol / gasoline)
Tip furca (Mast type)	Duplex
Sarcina maxima (Load capacity)	1300 kg (2,866 lb)
Punct centru greutate furci (Load centre)	500 mm (19.685 in)
Motor (Engine)	Isuzu 3LD1
Putere motor (Engine power)	32 CP (HP) 2700 RPM
Presiune motor hidraulic (Hydraulic pressure)	60 bar
Raza de intoarcere (Turning radius)	4000 mm
Greutate fara incarcatura (Empty load weight)	2300 kg
Greutate maxima cu incarcatura (Full load weight)	3600 kg
Punct centru greutate furci (Load centre)	500 mm
Distanta ridicare suporturi furca fara inaltare mast (Free lift)	150 mm
Inaltime maxima de ridicare (Max. lift height)	2.66 m
Lungime furca (Fork length)	1000 mm
Viteza de ridicare furca (Mast lifting speed)	33 m/min
Viteza de coborare furca (Mast lowering speed)	18 m/min
Rezervor ulei motor hidraulic (Hydraulic oil tank)	40 l
Tip baterie (battery type)	12 V 70AH

ALTE DETALII (OTHER DETAILS):

Motor Diesel (Diesel Engine)

3 cilindri, 4 timpi, racire cu apa. Pornire electrica. (Three-cylinder, four-stroke, water-cooled. Electric start) Radiatorul amesteca apa cu uleiul cu ajutorul unui ventilator electric (Radiator mixed water / oil with electric fan.)

Transmisie (Transmission)

Hidrostatica, pompa cu putere variabila si control electronic (Hydrostatic, variable displacement pump, electronic control and inching (approximation slow)) Motor hidrostatic cu 2 viteze, controlat electronic (Two-speed hydrostatic motor, electrically controlled) Presiune (Pressure): 345 bar

Presiune in pneuri (Tire pressure)

Fata (Front) 10.0/75-15.3 (10PR): presiune (Pressure): 5bar ± 0.5
Spate (Rear) 6.00-9 (10PR); presiune (Pressure): 8.5 bar ± 0.9 (2WD)
Spate (Rear) 23x8 ,50-12 (6PR); presiune (Pressure): 2.5 bar (4WD)

Temperatura (Temperature)

-15 ° C to 40 ° C.

Vibratii si nivel de zgomot (Vibration and noise levels)

In ambient (In the surroundings): Lwa = 104 dB (A) LpA = 85 dB (A)